



DASH 1600 Enclosure Specifications

- ❖ Measurements: 36" w x 39" d x 72" h
- ❖ 10 gauge steel construction
- ❖ 1" insulation throughout interior
- ❖ 1 weather tight door on rear with 2 recessed key locks, protected with non-drillable hard plate and high security hinges welded to frame and door.
- ❖ 2- 20Amp circuits
 - Circuit 1 lighting
 - Circuit 2 ATM
- ❖ Air Conditioner Option
- ❖ Heater Option
- ❖ Two tone color standard
- ❖ 3-4 coats of baked on high quality Acrylic Enamel
- ❖ Est. weight 850 lb.

DASH Security Features

- DASH utilizes a locker bar on its door that precludes access by a perpetrator. Even with the hinges removed, they can not gain access.
- Recessed non drillable locks, lock areas are protected with high manganese work- hardening armor. (The more they drill the harder the metal becomes.) The manganese plate is welded to our proprietary machined locking assembly which will not allow a drill bit to penetrate.
- Steel seams are welded inside and out, which means that the enclosure will not collapse inward if a chain is wrapped around it, preventing exposure of the ATM.
- Provides added security for business hour and level one ATM safes.
- DASH ATM manufactures the highest security ATM kiosks and enclosures on the market. To date, no criminal has ever gained entry into a DASH manufactured enclosure.

The DASH enclosure can be manufactured to accommodate any "Through-The-Wall" ATM currently on the market.